



KERA.Pro trouba/spoj K



KERA.Pro trouba/spoj S

KERA.PRO TROUBY | VYSOKÉ ZATÍŽENÍ

Jmeno- vitá světlost	Typ spoje	Spojovací systém	Průměr trouby		Průměr hrdla		Stavební délka	Hmotnost	Mezní únosnost ve vrch. zat.	Třída pevnosti
DN			Vnitřní d_1	Vnější d_3	Vnitřní d_4	Vnější d_8	l_1		FN	
			mm	mm	mm	mm	cm	kg/ks	kN/m	
200	S	C	200 ± 5,0	254 ± 5,0	275 ± 0,5	360	250	107	48	240
250	S	C	250 ± 6,0	318 ± 6,0	341,5 ± 0,5	440	250	188	60	240
250	K	C	250 ± 6,0	318 ± 6,0	341,5 ± 0,5	440	250	188	60	240
300	K	C	300 ± 7,0	376 ± 7,0	398,5 ± 0,5	510	250	250	72	240
300	S	C	300 ± 7,0	376 ± 7,0	398,5 ± 0,5	510	250	250	72	240
400	K	C	398 ± 8,0	492 ± 8,0	515,5 ± 0,5	650	250	379	80	200
400	S	C	398 ± 8,0	492 ± 8,0	515,5 ± 0,5	650	250	379	80	200
500	K	C	496 ± 9,0	609 ± 9,0	637 ± 0,5	790	250	575	80	160
500	S	C	496 ± 9,0	609 ± 9,0	637 ± 0,5	790	250	575	80	160
600	K	C	597 ± 12,0	725 ± 12,0	758 ± 0,5	930	250	780	96	160
600	S	C	597 ± 12,0	725 ± 12,0	758 ± 0,5	930	250	780	96	160
700	K	C	694 ± 12,0	832 ± 12,0	871 ± 0,5	1030	200	810	112	120
800	K	C	792 ± 12,0	932 ± 12,0	976 ± 0,5	1150	200	950	96	120