


Concealed System Simibox Light for bath and shower mixer with stopvalves 3.7898.0.000.100.1



TECHNICAL DATA

Order no.	3.7898.0.000.100.1
Connection	1/2" GN (one stopper 1/2" is included)
Flow rate	Spout: 21.9 l/min (3 bar)* Shower: 19.2 l/min (3 bar)* * except for the thermostatic models
Acoustic class	Spout: ID Shower: IC
Specification	Integrated stopvalves (for cold and warm water shut-off) Fitting depth of min. 74 mm Delivered with sealing sleeve and protective cap Flushing and fitting device premounted Matches all Laufen decors sets, both mechanical and thermostatic decor sets Suitable for all types of installation: mounting in, on or before wall Practical fitting aids, to be ordered separately

Mounting acc. excl.

Mounting aid for Simibox in/before wall,
order no. 3.7998.0.003.000.1
Additional mounting flanges, thickness 8 mm,
order no. 3.7998.0.000.500.1
Extension set for Simibox,
L = 25 mm – order no. 3.7998.0.000.050.1
L = 50 mm – order no. 3.7998.0.000.060.1
Rose spacer for Simibox,
L = 15 mm – order no. 3.7998.4.004.050.1
L = 30 mm – order no. 3.7998.4.004.060.1

TECHNICAL DRAWINGS

