



Product data sheet

Power tools for trade & industry

Cordless Rotary Hammer with SDS plus

GBH 185-LI



Evolve, with our most compact and ergonomic Boschhammer

The most important data

Battery voltage	18.0 V
Drilling dia. in concrete with hammer drill bits	4 – 22 mm
Impact rate at rated speed	0 – 4,675 bpm

Order number 0 611 924 021

Technical data

Additional data

Battery voltage	18.0 V
Tool holder	SDS plus
Impact rate at rated speed	0 – 4,675 bpm
Rated speed	0 – 1,050 rpm
Weight excl. battery	2.3 kg
BITURBO	No
Impact energy nominal	1.9 J

Drilling range

Drilling dia. in concrete with hammer drill bits	4 – 22 mm
Opt. app. range in concrete with hammer drill bits	4 – 12 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	14 m/s ²
Uncertainty K	1.5 m/s ²

Chiselling in concrete

Vibration emission value ah	9.4 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- More holes per charge and continuous power output thanks to motor with constant speed
- Better drilling experience due to Vibration Control, designed to absorb pulsation
- Enhanced safety against accidental jams thanks to KickBack Control
- Dust-free work condition with Auto Power GDE 12 extractor attachment

